

# 7-inch 2 MP 36X DarkFighter IR Network Positioning System



# 7-inch 2MP 36X DarkFighter IR Network Positioning System

## Main Features

- ✦ 1/1.8" progressive scan CMOS,
- ✦ Up to 1920 × 1080 @ 30 fps resolution,
- ✦ Min. illumination: Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0.001 Lux @(F1.6, AGC ON), 0 Lux with IR,
- ✦ 36 × optical zoom, 16 × digital zoom,
- ✦ 120 dB WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus,
- ✦ Up to 150 m IR distance,
- ✦ Support H.265+/H.265 video compression,

## Camera

---

- ✦ **Image Sensor** 1/1.8" progressive scan CMOS
  - ✦ **Max. Resolution** 1920 × 1080
  - ✦ **Min. Illumination** Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0.001 Lux @(F1.6, AGC ON), 0 Lux with IR
  - ✦ **Shutter Speed** 1/1s~1/30000 s
  - ✦ **Day & Night** Day, Night, Auto, Schedule
  - ✦ **Zoom** 36 × optical, 16 × digital
  - ✦ **Slow Shutter** Yes
- 

## Lens

---

- ✦ **Focal Length** 4.6~165.6 mm, 36 × optical
  - ✦ **FOV** Horizontal field of view: 55° to 2.0° (Wide-Tele)
  - ✦ **Focus** Auto/Semi-automatic/Manual
  - ✦ **Aperture** F1.6
  - ✦ **Zoom Speed** approx. 4.8 s
-

## Illuminator

---

- + **Supplement Light Type** IR
  - + **Supplement Light Range** 150 m
  - + **Smart Supplement Light** yes
- 

## PTZ

---

- + **Movement Range (Pan)** 360° endless
  - + **Movement Range (Tilt)** From +40° to -90° (auto flip)
  - + **Pan Speed**
- 

- ✓ Configurable, from 0.1°/s to 100°/s,
  - ✓ Preset speed: 100°/s
- 

- + **Tilt Speed**

---

- ✓ Configurable, from 0.1°/s to 50°/s
  - ✓ Preset Speed: 100°/s
- 

- + **Proportional Pan** yes
  - + **Presets** 300
  - + **Preset Freezing** yes
  - + **Patrol Scan** 8 patrols, up to 32 presets for each patrol
  - + **Pattern Scan** 4 pattern scans, record time over 10 minutes for each scan
  - + **Park Action** Preset/Pattern Scan/Patrol Scan/Auto Scan/Tilt Scan/Random Scan/Frame Scan/Panorama Scan
  - + **3D Positioning** yes
  - + **PTZ Status Display** yes
  - + **Scheduled Task** Preset/Pattern Scan/Patrol Scan/Auto Scan/Tilt Scan/Random Scan/Frame Scan/Panorama Scan/Dome Reboot/Dome Adjust/Aux Output
-

✚ **Power-Off Memory** yes

---

## Video

---

### ✚ **Main Stream**

---

✓ **50 Hz:** 25 fps (1920 × 1080, 1280 × 960, 1280 × 720)

✓ **60 Hz:** 30 fps (1920 × 1080, 1280 × 960, 1280 × 720)

---

### ✚ **Sub-Stream**

---

✓ **50 Hz:** 25 fps (704 × 576, 640 × 480, 352 × 288)

✓ **60 Hz:** 30 fps (704 × 480, 640 × 480, 352 × 240)

---

### ✚ **Third Stream**

---

✓ **50 Hz:** 25 fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288)

✓ **60 Hz:** 30 fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240)

---

### ✚ **Video Compression**

---

✓ **Main Stream:** H.265+/H.265/H.264+/H.264

✓ **Sub-stream:** H.265/H.264/MJPEG

✓ **Third Stream:** H.265/H.264/MJPEG

---

✚ **Video Bit Rate** 32 Kbps to 16384 Kbps

✚ **H.264 Type** Baseline Profile/Main Profile/High Profile

✚ **H.265 Type** Main Profile

✚ **Scalable Video Coding (SVC)** Support

✚ **Region Of Interest (ROI)** 8 fixed regions for each stream

---

## Audio

---

- ✚ **Audio Compression** G.711alaw, G.711ulaw, G.722.1, G.726, MP2L2,PCM
  - ✚ **Audio Bit Rate** 64 Kbps (G.711)/16 Kbps (G.722.1)/16 Kbps (G.726)/32-192 Kbps (MP2L2)
  - ✚ **Audio Sampling Rate** 8 kHz/16 kHz/32 kHz/48 kHz
  - ✚ **Environment Noise Filtering** yes
- 

## Network

---

- ✚ **Protocols** IPv4/IPv6, HTTP, HTTPS, 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour
  - ✚ **Simultaneous Live View** Up to 20 channels
  - ✚ **API** Open Network Video Interface (Version 19.12, Profile S, Profile G, Profile T), ISAPI, SDK, ISUP
  - ✚ **User/Host** Up to 32 users, 3 user levels: administrator, operator, and user
  - ✚ **Security** Password protection, complicated password, HTTPS encryption, 802.1X authentication (EAP-TLS, EAP-LEAP, EAP-MD5), watermark, IP address filter, basic and digest authentication for HTTP/HTTPS, RTP/RTSP over HTTPS, control timeout settings, security audit log, TLS 1.2, TLS 1.3, host authentication (MAC address)
  - ✚ **Network Storage** NAS (NFS, SMB/CIFS), auto network replenishment (ANR)
  - ✚ **Client** iVMS-4200, HikCentral Pro, Hik-Connect
  - ✚ **Web Browser** IE11, Chrome 57+, Firefox 52+, Safari 11+
- 

## Image

---

- ✚ **Image Parameters Switch** yes
  - ✚ **Image Settings** Saturation, brightness, contrast, sharpness, gain, and white balance adjustable by client software or web browser
  - ✚ **Day/Night Switch** auto
  - ✚ **Wide Dynamic Range (WDR)** 120 dB WDR
  - ✚ **SNR**  $\geq 52$ dB
-

- ✦ **Defog Digital Defog**
  - ✦ **Image Enhancement** HLC/BLC/3D DNR/Defog/EIS/Regional Exposure/Regional Focus
  - ✦ **Privacy Mask** 24 programmable polygon privacy masks, mask color or mosaic configurable
- 

## Interface

---

- ✦ **Ethernet Interface** 1 RJ45 10 M/100 M Ethernet
  - ✦ **On-Board Storage** support microSD / microSDHC / microSDXC cards, up to 256 GB
  - ✦ **Audio** 1-ch audio input and 1-ch audio output
  - ✦ **Alarm** 7-ch alarm input and 2-ch alarm output
  - ✦ **RS-485** 1 RS-485 (Half duplex, HIKVISION, Pelco-P, Pelco-D, self-adaptive)
- 

## Event

---

- ✦ **Basic Event** Motion detection, video tampering alarm, exception, alarm input and output
  - ✦ **Smart Event** Line crossing detection, intrusion detection, region entrance detection, region exiting detection, unattended baggage detection, object removal detection, audio exception detection
  - ✦ **Linkage** Manual tracking, Event tracking
  - ✦ **Smart Tracking** Upload to FTP/NAS/memory card, notify surveillance center, send email, trigger alarm output, trigger recording, and PTZ actions (such as preset, patrol scan, pattern scan)
- 

## Deep Learning Function

---

- ✦ **Face Capture** Support detecting up to 10 faces at the same time. Support detecting, tracking, capturing, grading, selecting of face in motion, and output the best face picture of the face.
- 

## General

---

- ✦ **Power** 24 VAC (Max. 55 W)
  - ✦ **Dimension**  $\Phi 181 \text{ mm} \times 396 \text{ mm} \times 377.5 \text{ mm}$  ( $\Phi 7.13'' \times 15.59'' \times 14.86''$ )
-

✚ **Weight** 7.6 kg (16.76 lb.)

✚ **Operating Condition** Temperature: Outdoor: -40°C to 70°C (-40°F to 158°F), Humidity: ≤ 90%

✚ **General Function** Anti-flicker, heartbeat, mirror, flash log, password reset via e-mail, pixel counter, password protection, one-key reset, three streams

---

## Approval

---

✚ **Protection** IP66, TVS 6000V Lightning Protection, Surge Protection and Voltage Transient Protection.

---