

2MP Smart Hybrid Light Audio Indoor Fixed Turret Camera



2MP Smart Hybrid Light Audio Indoor Fixed Turret Camera

Technical Specifications

- ✦ High quality imaging with 2 MP, 1920×1080 resolution,
- ✦ Up to 30 m IR distance for bright night imaging,
- ✦ 2.8 mm, 3.6 mm fixed focal lens,
- ✦ One port for four switchable signals (TVI/AHD/CVI/CVBS),
- ✦ Up to 20 m white light distance for bright night imaging,
- ✦ High quality audio with audio over coaxial cable, built-in mic,
- ✦ Water and dust resistant (IP67),
- ✦ Smart-Hybrid light, optimize your security with flexible lighting options,

Available Model - DS-2CE76D0T-LMFS(2.8mm)

Specifications

Camera

- ✦ **Image Sensor** 2 MP CMOS
 - ✦ **Max. Resolution** 1920 (H) × 1080 (V)
 - ✦ **Min. Illumination** 0.01 Lux @ (F1.6, AGC ON), 0 Lux with IR
 - ✦ **Shutter Time** PAL: 1/25 s to 1/50, 000 s; NTSC: 1/30 s to 1/50, 000 s
 - ✦ **Day & Night** ICR
 - ✦ **Angle Adjustment** Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360°
 - ✦ **Signal System** PAL/NTSC
-

Lens

- ✦ **Lens Type** 2.8 mm, 3.6 mm fixed focal lens
 - ✦ **Focal Length & FOV**
-

- ✓ 2.8 mm, horizontal FOV: 101°, vertical FOV: 56°, diagonal FOV: 118°
 - ✓ 3.6 mm, horizontal FOV: 78°, vertical FOV: 42°, diagonal FOV: 92°
-

Lens Mount M12

Illuminator

Supplement Light Type White Light; IR

Supplement Light Range

- ✓ IR : Up to 30 m
 - ✓ White Light : Up to 20 m
-

Image

Image Settings Brightness, Sharpness, Smart IR

Frame Rate

- ✓ TVI: 1080P @ 30 fps, 1080P @ 25 fps
 - ✓ AHD: 1080P @ 30 fps, 1080P @ 25 fps
 - ✓ CVI: 1080P @ 30 fps, 1080P @ 25 fps
 - ✓ CVBS: PAL/NTSC
-

Day/Night Mode Auto/Color/BW (Black and White)

Wide Dynamic Range (WDR) Digital WDR

Image Enhancement DWDR/BLC/HLC/Global

White Balance Auto/Manual

AGC Yes

Interface

- + **Video Output** Switchable TVI/AHD/CVI/CVBS
 - + **Built-In Microphone** Yes
-

General

- + **Material** Metal
 - + **Dimension** 80 mm × Ø85.1 mm (3.1" × Ø3.4")
 - + **Weight** Approx. 296 g (0.65 lb.)
 - + **Operating Condition** -40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
 - + **Communication** HIKVISION-C
 - + **Language** English
 - + **Power Supply**
-

- ✓ 12 VDC ± 25%

- ✓ *You are recommended to use one power adapter to supply the power for one camera.

- + **Consumption** Max. 3.3 W
-

Approval

- + **Protection** IP67
-