

7-inch 4MP 32X Powered By DarkFighter IR Network Speed Dome



7 inch 4MP 32X Powered by DarkFighter IR Network Speed Dome

Main Features

- ✦ 1/1.8" progressive scan CMOS
- ✦ High quality imaging with 4 MP resolution
- ✦ Excellent low-light performance with powered-by-DarkFighter technology
- ✦ Audio visual alarm: The white flashing light and audible warning can be triggered by certain events
- ✦ 32× optical zoom and 16× digital zoom provide close up views over expansive areas
- ✦ Expansive night view with up to 200 m IR distance
- ✦ Focuses on human and vehicle targets classification based on deep learning
- ✦ Face capture: Up to 5 faces captured at the same time

Camera

- ✦ **Image Sensor** 1/1.8" progressive scan CMOS
- ✦ **Max. Resolution** 2560 × 1440
- ✦ **Min. Illumination** Color: 0.005 Lux @ (F1.5, AGC ON), B/W: 0.001 Lux@(F1.5, AGC ON), 0 Lux with IR
- ✦ **Shutter Speed** 1/1 s to 1/30000 s
- ✦ **Day & Night** IR cut filter
- ✦ **Zoom** 32x optical, 16x digital
- ✦ **Slow Shutter** Yes
- ✦ **DORI**

- ✓ Detect (25px/m): 2046.9 m
 - ✓ Observe (63px/m): 812.3 m
 - ✓ Recognize (125px/m): 409.4 m
 - ✓ Identify (250px/m): 204.7 m
-

Lens

✚ **Focal Length** 5.9 mm to 188.8 mm

✚ **FOV**

✓ Horizontal field of view: 50.8° to 2.6° (wide-tele),

✓ Vertical field of view: 29.4° to 1.5° (wide-tele),

✓ Diagonal field of view: 57.4° to 3° (wide-tele)

✚ **Focus** Auto,semi-auto,manual

✚ **Aperture** Max. F1.5

✚ **Zoom Speed** Approx. 4.8 s

Illuminator

✚ **Supplement Light Type** IR

✚ **Supplement Light Range** IR Distance: up to 200 m

PTZ

✚ **Movement Range (Pan)** 360°

✚ **Movement Range (Tilt)** -15° to 90° (auto flip)

✚ **Pan Speed** Pan speed: configurable from 0.1° to 160°/s; preset speed: 240°/s

✚ **Tilt Speed** Tilt speed: configurable from 0.1° to 120°/s, preset speed 200°/s

✚ **Proportional Pan** Yes

✚ **Presets** 300

✚ **Preset Freezing** Yes

✚ **Patrol Scan** 8 patrols, up to 32 presets for each patrol

✚ **Pattern Scan** 4 pattern scans

✚ **Park Action** Preset, pattern scan, auto scan, tilt scan, random scan, frame scan, panorama scan

+ **3D Positioning** Yes

+ **PTZ Status Display** Yes

+ **Scheduled Task** Preset, pattern scan, patrol scan, auto scan, tilt scan, random scan, frame scan, panorama scan, dome reboot, dome adjust, aux output

+ **Power-Off Memory** Yes

Video

+ **Main Stream**

✓ 50 Hz: 25 fps (2560 × 1440, 1920 × 1080, 1280 × 960, 1280 × 720)

✓ 60 Hz: 24 fps (2560 × 1440, 1920 × 1080, 1280 × 960, 1280 × 720)

+ **Sub-Stream**

✓ 50 Hz: 25 fps (704 × 576, 640 × 480, 352 × 288)

✓ 60 Hz: 24 fps (704 × 480, 640 × 480, 352 × 240)

+ **Third Stream**

✓ 50 Hz: 25 fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288)

✓ 60 Hz: 24 fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240)

+ **Video Compression**

✓ Main stream: H.265+/H.265/H.264+/H.264

✓ Sub-stream: H.265/H.264/MJPEG

✓ Third stream: H.265/H.264/MJPEG

+ **Video Bit Rate** 32 kbps to 16384 kbps

+ **H.264 Type** Baseline Profile/Main Profile/High Profile

- ✦ **H.265 Type Main Profile**
 - ✦ **Scalable Video Coding (SVC)** H.264 and H.265 encoding
 - ✦ **Region Of Interest (ROI)** 8 fixed regions for each stream
-

Audio

- ✦ **Audio Compression** G.711alaw, G.711ulaw, G.722.1, G.726, MP2L2, AAC, PCM
 - ✦ **Audio Bit Rate** 64 Kbps (G.711)/16 Kbps (G.722.1)/16 Kbps (G.726)/32-192 Kbps (MP2L2)/16-64 Kbps (AAC)
 - ✦ **Audio Sampling Rate** 8 kHz/16 kHz/32 kHz/48 kHz
 - ✦ **Environment Noise Filtering** Yes
-

Network

- ✦ **Protocols** IPv4/IPv6, HTTP, HTTPS, 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour
 - ✦ **Simultaneous Live View** Up to 20 channels
 - ✦ **API** Open Network Video Interface (Version 19.12, Profile S, Profile G, Profile T), ISAPI, SDK, ISUP
 - ✦ **User/Host** Up to 32 users, 3 user levels: administrator, operator, and user
 - ✦ **Security** Password protection, complicated password, HTTPS encryption, 802.1X authentication (EAP-TLS, EAP-LEAP, EAP-MD5), watermark, IP address filter, basic and digest authentication for HTTP/HTTPS, RTP/RTSP over HTTPS, control timeout settings, security audit log, TLS 1.2, TLS 1.3, host authentication (MAC address)
 - ✦ **Network Storage** NAS (NFS, SMB/CIFS), auto network replenishment (ANR)
 - ✦ **Client** iVMS-4200, HikCentral Pro, Hik-Connect
 - ✦ **Web Browser** IE11, Chrome 57+, Firefox 52+, Safari 11+
-

Image

- ✦ **Image Settings** Saturation, brightness, contrast, sharpness, gain, and white balance adjustable by client software or web browser
-

- ✦ **Day/Night Switch** Day, Night, Auto, Schedule
 - ✦ **Wide Dynamic Range (WDR)** 120 dB
 - ✦ **SNR** > 52 dB
 - ✦ **Defog** Digital defog
 - ✦ **Image Stabilization** EIS
 - ✦ **Image Enhancement** BLC, HLC, 3D DNR
 - ✦ **Privacy Mask** 24 programmable polygon privacy masks, mask color or mosaic configurable
 - ✦ **Regional Focus** Yes
 - ✦ **Regional Exposure** Yes
-

Interface

- ✦ **Ethernet Interface** 1 RJ45 10M/100M self-adaptive Ethernet port
 - ✦ **On-Board Storage** Built-in memory card slot, support microSD/SDHC/SDXC card, up to 256 GB
 - ✦ **Built-In Speaker** 1 built-in speaker with effective distance reaching max. 30 meters
 - ✦ **Audio** 1 input (line in), max. input amplitude: 2-2.4 vpp, input impedance: $1\text{ k}\Omega \pm 10\%$; 1 output (line out), line level, output impedance: $600\ \Omega$
 - ✦ **Alarm** 2 inputs, 1 output
 - ✦ **Reset** Yes
-

Event

- ✦ **Basic Event** Motion detection, video tampering alarm, exception, alarm input and output
 - ✦ **Smart Event** Line crossing detection, intrusion detection, region entrance detection, region exiting detection, unattended baggage detection, object removal detection, audio exception detection
 - ✦ **Linkage** Upload to FTP/NAS/memory card, notify surveillance center, send email, trigger alarm output, trigger recording, audible warning, white light flashing, and PTZ actions (such as preset, patrol scan, pattern scan)
 - ✦ **Smart Tracking** Manual tracking, auto-tracking
-

Deep Learning Function

+ Face Capture

- ✓ Detects up to 5 faces simultaneously.
 - ✓ Supports detecting, capturing, grading, selecting of face in motion, and output the best face picture of the face
-

+ Perimeter Protection

- ✓ Line crossing, intrusion, region entrance, region exiting
 - ✓ Support alarm triggering by specified target types (human and vehicle)
-

General

+ Power

- ✓ 24 VAC, max. 42 W (including max. 18 W for IR and max. 10 W for heater);
 - ✓ Hi-PoE
-

+ **Dimension** \varnothing 220 mm × 363.3 mm (\varnothing 8.66" × 13.91")

+ **Weight** Approx. 5 kg (11.03 lb.)

+ **Material** ADC12

+ **Operating Condition** -30 °C to 65 °C (-22 °F to 149 °F). Humidity 90% or less (non-condensing)

+ **Demist** Yes

Approval

+ EMC

- ✓ FCC SDoC (47 CFR Part 15, Subpart B);
-


- ✓ CE-EMC (EN 55032: 2015, EN 61000-3-2: 2019, EN 61000-3-3: 2013, EN 50130-4: 2011 +A1: 2014);
 - ✓ RCM (AS/NZS CISPR 32: 2015);
 - ✓ IC VoC (ICES-003: Issue 6, 2019);
 - ✓ KC (KN 32: 2015, KN 35: 2015)
-

Safety

- ✓ UL (UL 62368-1);
 - ✓ CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013, IEC 62368-1:2014);
 - ✓ CE-LVD (EN 62368-1:2014+A11:2017);
 - ✓ BIS (IS 13252(Part 1):2010+A1:2013+A2:2015);
 - ✓ LOA (SANS IEC60950-1)
-

Environment

- ✓ CE-RoHS (2011/65/EU); WEEE (2012/19/EU);
 - ✓ Reach (Regulation (EC) No 1907/2006)
-

 **Protection** IP66 (IEC 60529-2013), IK10 (excluding glass window), TVS 6000V lightning protection, surge protection and voltage transient protection
